

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**



THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H04N 9/04	A1	(11) International Publication Number: WO 92/10066 (43) International Publication Date: 11 June 1992 (11.06.92)
(21) International Application Number: PCT/US91/08845 (22) International Filing Date: 25 November 1991 (25.11.91) (30) Priority data: 617,731 26 November 1990 (26.11.90) US (71) Applicant: EASTMAN KODAK COMPANY [US/US]; 343 State Street, Rochester, NY 14650-2201 (US). (72) Inventor: JACKSON, Todd, Alan ; 6 Peachtree Lane, Pitts- ford, NY 14534 (US). (74) Agent: DUGAS, Edward; 343 State Street, Rochester, NY 14650-2201 (US).		(81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: SPECTRALLY SELECTIVE DITHERING AND COLOR FILTER MASK FOR INCREASED IMAGE SENSOR BLUE SENSITIVITY

**(57) Abstract**

An improved method of operating a color scanning system of the type that incorporates a monochrome image sensor having at least one photosensitive area that is sequentially exposed to individual colors of a scene and to a dithering of the scene with respect to the image sensor photosensitive area is described along with an improved color filter mask for the at least one photosensitive area. The blue filter mask is formed over a portion of the photosensitive area, for example, an L-shaped portion, that covers approximately 25 % of the photosensitive area. The method of operation is to first image and dither a red filtered version of the scene onto the photosensitive area to generate a red image signal. Next a green filtered version of the scene is imaged and dithered onto the photosensitive area to generate a green image signal, and lastly a blue filtered version of the scene is imaged onto the photosensitive area without dithering to generate a blue image signal. The photosensitive area generates an electrical signal from its full area in this mode, because the blue masking material is transparent to the blue image.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TC	Togo
DE ⁺	Germany	MC	Monaco	US	United States of America
DK	Denmark				

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

SPECTRALLY SELECTIVE DITHERING AND COLOR FILTER MASK
FOR
INCREASED IMAGE SENSOR BLUE SENSITIVITY

5 Field of Invention

 The present invention is related to the field
of color image sensors and more particularly to a
multi-element solid state color sensor having a color
filter mask mounted thereon and an associated dithering
10 method.

Background of the Invention

 In the image sensor art there is a continual
drive towards increasing the resolution of the image
15 sensor so that in turn higher resolution hard and soft
copies of the sensed images can be formed. One of the
techniques that has received wide spread use in the
digital image processing industry involves a process
called dithering. The term was first used to define a
20 periodic controlled jitter type motion that was applied
to servo motors to decrease the stiction effect between
mechanical pieces. In the image processing art the
term is used to describe the movement of an image
carrying beam from a reference scanning path for a
25 first pass over the image sensor to a displaced path
for a second pass. The displacement between the two
paths is fixed such that the portion of the image,
formed in the beam, that impinges onto the spacing
between each of the photosensitive elements that form
30 the sensor array on the first pass impinges on the
photosensitive elements on the second or subsequent
passes. The process of dithering is thus employed to
increase the effective resolution of an image sensor.
Another way to conceptualize the basic process is one
35 wherein a small single sensor is moved to different

positions on an image thereby collecting data at each position. Such a process is shown pictorially in Figure 1. This process can be extended to image sensors which are composed of a regular matrix array of individual photosensitive elements. In a typical two-dimensional dithering application, each individual sensor in a matrix array is employed to obtain information at each of four non-overlapping adjacent picture elements (pixels). Since four times as much information is gathered as there are elements in the imager, the effective resolution of the imager is multiplied by four.

Two-dimensional dithering is performed straightforwardly when the photosensitive area of the sensor elements used to acquire each pixel of an image are square and the imager has a fill factor of $(100\%)/n^2$ where n is an integer. For example, when $n=2$, the sensor has a fill factor of 25%, and non-overlapping adjacent pixel locations are readily obtained in the image with two-dimensional dithering.

When one desires to increase the resolution of an imager possessing either a high fill factor and/or non-square sensor elements, one typically masks off a portion of the photosensitive area in each of the individual sensor elements to achieve the proper fill factor and a square aspect ratio. This is illustrated in Figure 2a and 2b. One consequence of this masking is a reduction in the imager sensitivity proportional to the percentage of the masked area of the sensors. This is especially of concern for CCD imagers which typically exhibit a low sensitivity in the blue (400-500 nm) part of the visible spectrum.

In U.S. Patent No. 4,710,803 entitled "Color Filter and Color Image Sensor Using the Same" by Suzuki et al. there is disclosed a color sensor array wherein the photosensitive elements representing a pixel

element are covered with three L-shaped filter masks representing the primary colors R, G, and B. This configuration is urged for saving electrical wiring and for providing a more consistent exposure of each of the individual filter masked elements to the same portion of the original image.

Another patent of interest for its teaching in this area is U.S. Patent No. 4,481,530 entitled "Color Filter Arrangement for Optoelectric Converting Device" by Wagensonner et al. In that patent it is recognized that the area of a photosensitive element assigned to collect the green components of an image has to be different in size than the area assigned for the blue and red and in a like manner the red area has to be different in size from the blue. The main reason for this difference is that the photosensitive elements forming the sensor respond to the different frequencies of light in a different manner, i.e. green light provides a greater electrical output than for example blue light. Another reason for this difference is that the human eye also does not treat each of the colors with the same degree of responsiveness. A color image formed from equally weighted sensor signals would therefor not appear correct to the human eye. Although the referenced patent deals with the responsiveness of the photosensitive material to the frequency of the impinging light by adjusting the area of each sensor according to the color it is to detect, it would also be obvious that the area can be held constant and that the signals from each sensing element could be weighted to provide the same effect.

SUMMARY OF THE INVENTION

The preferred embodiment of the present invention is directed towards providing a high blue sensitivity CCD imager, particularly adapted for use in

a system that captures color images one color at a time using a dithering feature. Recognizing that the acutance of the human visual system (HVS) in the blue part of the spectrum is about 1/20th that of its red and green acutance. It thus follows, that one may suffer no loss of image sharpness by not dithering when acquiring the blue image information as the HVS cannot perceive the increased resolution. With this in mind, an improved CCD image sensor would have close to a 100% fill factor which would then be reduced to a 25% fill factor using a blue transmittance filter as a mask. Thus, when acquiring blue information from the image sensor without dithering, the filter/mask is transparent and the image sensor sensitivity is high since a larger area of the image sensor is active. When acquiring red or green image information, the filter/mask blocks the light reducing the active image sensor area thereby allowing dithering to be performed.

From the foregoing it can be seen that a primary object of the present invention is the provision of an improved color image sensor.

It is a further object of the present invention to provide a color image sensor which is particularly adapted to be used in a dithering scheme.

It is yet another object of the present invention to provide an image sensor that sports an effectively increased area for blue light while maintaining the effective areas for red and green light at a lesser and substantially equal value.

These and other objects of the present invention will become more apparent when taken in conjunction with the following description and drawings wherein like characters indicate like parts and which drawings form a part of the present specification.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates the positioning of one square photosensitive element in four positions with respect to an image.

5 Figures 2a and 2b illustrate a rectangular sensor element, and an L-shaped blue filter mask positioned over the rectangular sensor-element of Figure 2a, respectively.

10 Figure 3 is a perspective view of the rectangular sensor and the L-shaped filter mask shown in Figure 2.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figure 1, the technique of
15 dithering is illustrated with an image sensor element 20 being shown positioned sequentially in four positions. At each position the image sensor element is activated to capture that portion of the image that is within its field of view. The state of the art is
20 such that the image sensor and the image do not have to be moved but instead the illumination (scanning) beam reflecting from the image is deflected by a deflecting device such as a rotating mirror to effectively achieve the desired repositioning of the image sensor with
25 respect to the image. Although only one image sensor element is shown it is well known that there are a large number of such elements that are used to form a complete image sensor and that the showing of one is only for the purpose of simplicity. In a complete
30 image sensor the elements are photosensitive devices such as diodes which are deposited next to each other in matrix array with each device providing an electrical signal output to a CCD as a function of the intensity of the light impinging thereon. Each
35 photosensitive device has a photosensitive area for receiving the light.

Figure 2A illustrates a rectangular image sensor's photosensitive area 22. In Figure 2B the photosensitive area 22 is masked to a square area, approximately 25% of the total area, by the use of a blue filter mask 30. Figure 3 illustrates the arrangement in perspective view.

In the preferred embodiment of the invention the L-shaped blue filter mask material is positioned over each of the photosensitive elements that form the image sensor. An acceptable masking material is any material with a high transmissivity in the 400 - 500 nm wavelength range and low transmissivity elsewhere. Such a material is described as an organic blue dye in U.S. Patent No. 4,355,087, Columns 8 and 9. The teachings of that patent are incorporated into the present Application, by reference.

In the method of operation of the present invention, the blue image is formed by passing the image beam through a blue transmitting filter and onto the imager. The imager's photosensitive elements acquire image information through their L-shaped blue masked areas and the unmasked areas. Since the photosensitive areas are adjacent, the fill factor is 100% and sensitivity is high. Dithering is not performed.

The green image is formed by passing the image beam through a green transmitting filter and onto the imager. The individual blue L-shaped masks on the photosites are non-transmitting to the green image beam so that only the non-masked areas of the photosensitive elements receive the image. Dithering is then performed to acquire the green image information with increased resolution.

The red image is formed in the same way as is the green image except that the image beam is passed through a red transmitting filter onto the imager. The

filters that are passed in front of the imager's photosensitive elements may be mounted in a filter wheel of the type described in U.S. Patent No. 4,967,264, entitled "Color Sequential Optical Offset Image Sampling System" by Parulski et al. The teachings of that patent are incorporated herein by reference along with the teachings of U.S. Patent Nos. 4,638,371 and 4,755,876. The aforementioned three patents are assigned to Eastman Kodak Co. as is the present Application. The signals generated by the photosensitive elements are then combined by apparatus and methods well known to persons in the art to form through a display and or printing device a viewable color image.

While there has been disclosed what is considered to be the preferred embodiment of the invention, it will be manifest that many changes and modifications may be made therein without departing from the essential spirit of the invention. It is intended, therefore, in the annexed claims to cover all such modifications as may fall within the true spirit of the invention.

I CLAIM:

1. A solid state color imaging sensor
having at least one photosensitive area for converting
5 incident light into electrical signals; and
a blue filter masking material positioned
over a portion of said photosensitive area.

2. The solid state imaging sensor according
10 to Claim 1 wherein said photosensitive area is
rectangular in shape and said blue filter masking
material is L-shaped.

3. The solid state image sensor according
15 to Claim 2 wherein said blue filter masking material is
configured on said photosensitive area so as to leave a
square portion of said photosensitive area unmasked.

4. An improved method of operating a color
20 scanning system of the type that incorporates a
monochrome image sensor having at least one
photosensitive area that is sequentially exposed to
individual colors of a scene and to a dithering of the
scene with respect to the image sensor photosensitive
25 area comprising the steps of:

forming a blue filter mask over a portion
said photosensitive area;




imaging and dithering a red filtered version
of said scene onto said photosensitive area to generate
30 a red image signal;

imaging and dithering a green filtered
version of said scene onto said photosensitive area to
generate a green image signal; and

imaging a blue filtered version of the scene
35 onto the photosensitive area, without dithering, to
generate a blue image signal.

5. The method according to Claim 4 wherein said blue filter mask is formed in an L-pattern over a rectangular photosensitive area to form an unmasked
5 square photosensitive area.

6. The method according to Claim 4 wherein said blue mask covers approximately 25% of the photosensitive area.

**FIG. 1****FIG. 2A****FIG. 2B**





FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 91/08845

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC Int. Cl. 5 H 04 N 9/04		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int. Cl. 5	H 04 N	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	Patent Abstracts of Japan, vol. 6, no. 64 (E-103)[942], 23 April 1982, & JP,A,574679 (MATSUSHITA DENKI SANGYO K.K.) 11 January 1982, see the whole abstract ---	1
A	---	3
X	Patent Abstracts of Japan, vol. 7, no. 208 (E-198)[1353], 14 September 1983, & JP,A,58104586 (MATSUSHITA DENKI SANGYO K.K.) 22 June 1983, see the whole abstract ---	1
A	---	3
A	US,A,4967264 (PARULSKI et al) 30 October 1990, see column 2, lines 11-39 (cited in the application) -----	4
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>⁹ Special categories of cited documents : ¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
27-02-1992	24.04.92	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE		

US 9108845
SA 54467

EPC FORM 10479

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)